

111AF Quick-Drying Asphalt Primer

DESCRIPTION:

Karnak #111AF is a general purpose, Quick-Drying penetrating asphalt primer specially formulated for the preparation of all types of surfaces prior to the application of hot or cold asphalt systems and/or coatings. Karnak 111AF Quick-Drying Asphalt Primer is prepared from a blend of highly ductile, soft and high melting-point asphalts in a refined solvent.

USES:

Karnak #111AF Quick-Drying Asphalt Primer is specially designed for use as a quick-drying general utility prime coat for concrete, gypsum, masonry, brick and metal surfaces over which waterproofing, dampproofing, roof coatings and other asphaltic products are to be applied. This primer readily penetrates pores and seals dusty masonry surfaces to provide a firm base for coatings. It is specified as a quick drying (approximately 4 hours) prime coat prior to the application of a membrane waterproofing system on all concrete structures. Karnak #111AF Quick-Drying Asphalt Primer is also very effectively used as a quick-drying felt primer on old dried out built-up roofs where penetration is required to revitalize the base surfaces before roof coatings or cold applied systems are applied.

SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil, grease, dust, dirt, loose paint or other foreign matter.

APPLICATION:

Easily applied by brush or spray equipment at the rate of 0.5 gallon per 100 sq. ft. depending upon porosity and type of surface being primed. Masonry and dried out built-up roof structures should be fully coated to ensure proper penetration so that an effective bond can be achieved for the covering material.

COVERAGE:

Apply at the rate of 0.5 gallon per 100 sq. ft.

CURE TIME:

Approximately 2 to 4 hours @ 77°F / 50% relative humidity.

CARE OF TOOLS:

Brushes and other tools may be thoroughly cleaned after use with mineral spirits, taking the necessary precautions when handling combustible materials.

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066 732-388-0300

• 800-526-4236 • FAX: 732-388-9422 WEB:

<http://www.karnakcorp.com>

111AF Quick-Drying Asphalt Primer

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.


KARNAK