

118 Black Asphaltum

DESCRIPTION:

Karnak #118 Black Asphaltum is a special formulated **QUICK-DRYING** general purpose black asphalt paint. It is prepared from a selected, high melting-point asphalt, carefully admixed with a pure hydrocarbon solvent to a paint consistency. It will withstand the rigors of hot summer temperatures without sagging or running. It provides excellent protection against weather and corrosion.

USES:

Karnak #118 Black Asphaltum has wide use as a general purpose black asphalt coating on all surfaces. It provides excellent protection for aluminum window frames and other metals when placed in contact with masonry walls. It will also help prevent corrosion and decay on storage tanks, railings, pipe and exterior duct work.

SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil, grease, dust, dirt, loose paint or other foreign matter.

COVERAGE:

Easily applied by brush or spray equipment at the rate of 1 to 1.5 gallons per 100 sq. ft.

SPECIFICATIONS:

Federal Spec:	TT-C-494
Federal Spec:	FF-H-C-494
Military Spec:	Mil-C-16173D

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>