

16 Double Coverage Cement

DESCRIPTION:

Karnak #16 Double Coverage Cement is manufactured from a blend of selected asphalts, mineral fillers and refined solvents. This composition is then passed through a high speed mixer which provides a smooth consistency product, free of foreign matter and lumps.

USES:

1. Lap cement
2. Rolled roofing adhesive
3. Blind nailing cement

SURFACE PREPARATION:

Karnak #16 Double Coverage Cement is applied by brush, broom or squeegee. The area to be coated must be free and clean of all debris, dust and dirt.

COVERAGE:

Under normal conditions, Karnak #16 Double Coverage Cement should be applied at the rate of 2 to 3 gallons per 100 sq. ft.

SPECIFICATIONS:

ASTM D-3019 Type III

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

CARE OF TOOLS:

Tools may be thoroughly cleaned after use with mineral spirits or petroleum solvents, taking the due precautions necessary when handling combustible materials.

PACKAGING:

Available in 5 gallon pails and 1 gallon pails.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

