

160.1 Amphibicaulk (wet and dry)

DESCRIPTION:

Karnak #160.1 Amphibicaulk is a carefully prepared caulking-grade roof cement with special water displacing characteristics, which ensures an effective bond to both wet and dry surfaces. The ability to adhere during inclement weather conditions makes Karnak #160.1 Amphibicaulk the first choice of both roofing contractors and plant engineers. Karnak #160.1 Amphibicaulk is composed of selected asphalt, mineral fillers combined with refined solvent, and special chemical ingredients, which give it a unique water displacement quality.

USES:

Karnak #160.1 Amphibicaulk is a cold process, heavy bodied, caulk-grade roof cement ideal for sealing leaks in and around asphalt built-up roofs, joints, chimney cracks, skylights, vents, down-spouts and gutters. The dried film retains its flexibility and ductility, so the caulking will resist extreme variations in temperature and weather. Karnak #160.1 Amphibicaulk may also be used to improve wind resistance on low slope shingle roofs.

SURFACE PREPARATION:

All surfaces should be clean and free from oil, grease, rust, dirt, and other foreign matter. Excess water should be removed, if possible, before application of Karnak #160.1 Amphibicaulk.

APPLICATION:

Karnak #160.1 Amphibicaulk is ready to use directly from the container. No heating is required. Apply Karnak #160.1 Amphibicaulk directly over the cracks with a caulking gun.

SPECIFICATIONS:

ASTM D-4586 Type I Class I & Class II

ASTM D-3409

Federal Specification SS-C-153 Type I (except Non-Asbestos)

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066

732-388-0300 • 800-526-4236 • FAX: 732-388-9422

WEB: <http://www.karnakcorp.com>

160.1 Amphibicaulk (wet and dry)

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

CARE OF TOOLS:

Caulking guns and equipment should be thoroughly cleaned with mineral spirits, taking necessary precautions when handling combustible materials.

PACKAGING:

Available in 10.1 oz. caulking cartridges.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.