

18 Perfectseal Flashing Cement (Asbestos-free)

DESCRIPTION:

Karnak #18 Perfectseal Flashing Cement is a scientifically compounded composition of selected asphalts, mineral fibers, and refined solvents that are manufactured to a heavy consistency. Designed for application by trowel #18 is a durable cement with excellent adhesion and weathering characteristics. This product when applied dries to a tough, flexible, water resistant and corrosion proof coating that provides excellent performance over a wide range of temperature and weather conditions. Available in three consistencies: Summer, Semi and Winter.

USES:

Karnak #18 Perfectseal Flashing Cement is a general purpose cement for repairing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, down- spouts and cornices. Excellent for sealing cracks in concrete, brick, as a joint filler for pre-cast roof slabs and general purpose use in maintenance of exposed buildings and structures.

SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil or grease, dust, dirt, loose paint or other foreign matter prior to application.

APPLICATION:

Spread Karnak #18 Perfectseal Flashing Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, spread Karnak #18 Perfectseal Roof Cement over the damaged area, then embed Karnak Cotton, Glass or Poly-Mat Membrane reinforcement and then apply another coat of Karnak #18 Perfectseal Roof Cement over the entire patch.

PRODUCT SPECIFICATIONS:

ASTM D-4586, Type I Class I

Fed. Spec. SS-C-153 Type 1 (except non-Asbestos)

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



18 Perfectseal Flashing Cement (Asbestos-Free)

PHYSICAL PROPERTIES:

1. Consistency: A smooth, heavy trowel consistency which will readily spread on and adhere to surfaces without sagging.
2. Character of Dried Film: Uniform, excellent adhesion to masonry, steel, cured concrete, shingles, asphalt roofing and a variety of other surfaces.
3. Has excellent resistance to flow at high temperatures when used on a vertical surface.

CAUTION:

Do not use near heat or open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Avoid getting in eyes. Use only with adequate ventilation. Cover air intakes during application and while drying.

CARE OF TOOLS:

Tools and other equipment should be thoroughly cleaned with mineral spirits or petroleum solvents, taking necessary precautions when handling combustible materials.

PACKAGING:

Available in 5 gallon pails and 3 gallon buckets.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

