## 229AR Elastomeric

Trowel Grade – Apply to either vertical or horizontal surfaces using a smooth edge trowel. Coverage will vary depending on the desired thickness. To achieve a 1/16" thickness apply at the rate of 4 gallons per 100 sq. ft.; 1/8" thickness apply at the rate of 8 gallons per 100 sq. ft.; 1/4" thickness apply in two coats at the rate of 8 gallons per 100 sq. ft. per coat.

Brush Grade – Mix thoroughly just prior to using. Apply to horizontal roof surfaces with a fiber roof brush at the rate of 3 to 4 gallons per 100 sq. ft. Coverage will vary depending on the irregularity and porosity of the roof surface.

Caulk Grade – Apply directly in and over cracks using a standard caulking gun. An application rate of  $\frac{1}{4}$ " x  $\frac{1}{4}$ " bead of caulk will yield approximately 75 linear feet per 30 oz. caulking cartridge. Coverage may vary depending on desired thickness and surface being caulked.

### **SPECIFICATIONS:**

ASTM D-4586 Type I Class I ASTM D-4479 Type I ASTM D-3409

Complies with CH. 13 of Massachusetts Energy Code

#### PHYSICAL PROPERTIES:

Weight Per Gallon: 8.6 lbs.

Hardness, Shore A: 55 ASTM D-2240 Elongation: 350% ASTM D-412 Tensile Strength, PSI: 400 ASTM D-412

Color: Black

Water Vapor Permeance: 0.017 perm ASTM E-96

Air Permeability (Leakage): 0.000 L/(s·m2) @ pressure difference of 75 Pa

Service Temp. Range: -40°F to 160°F

Solids: Trowel 70%, Brush 63%, Spray 60% ASTM D-2697 VOC Content: Please visit www.karnakcorp.com for latest VOC

content as products are updated to comply with the

most current VOC regulations





# 229AR Elastomeric

### **CAUTION:**

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner.

### **CARE OF TOOLS:**

Tools and other equipment should be thoroughly cleaned with 709 Karna-Klean. Mineral spirits or similar solvent may also be used, taking necessary precautions when handling combustible material.

### **PACKAGING:**

Available in 1 gallon, 3 gallon & 5 gallon pails, 55 gallon drums and 30 oz. caulking cartridges

Please see page 222 for additional mold and safety information.



