

41 WEB-Caulk (Water-Based Elastomeric Barrier, Low VOC)

DESCRIPTION:

Karnak 41 WEB-Caulk is a single component, elastomeric asphalt emulsion caulk-grade cement for roofing, dampproofing, and waterproofing. This smooth and easy to gun caulk gun dries to a durable sealant exhibiting excellent strength and adhesion. 41 WEB-Caulk outperforms traditional asphalt flashing cement caulks in performance and longevity.

FEATURES, BENEFITS AND ADVANTAGES:

- Excellent Adhesion
- Improves Weather and Water Resistance
- Sag Resistant
- Low Odor
- Outstanding Flexibility
- Will Not Shrink or Crack
- Meets ASTM D-1227 Type II Class I
- VOC Compliant, CARB and SCAQMD Compliant

USES:

Karnak 41 WEB-Caulk is a general purpose flashing cement caulk for repairing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices. Use to seal cracks in concrete and brick and as a joint filler for precast roof slabs and for flashing details on asphalt roofs as well as for general purpose use in the maintenance of exposed buildings and structures. Do not use in areas subject to water ponding.

SURFACE PREPARATION:

All surfaces to be caulked must be dry, clean and free from mildew, loose paint or coatings, oil, grease, rust, dirt, and other foreign matter.

APPLICATION:

Cut spout at an angle to desired bead size and load into a standard caulking gun. Karnak 41-WEB Caulk should be applied with even pressure directly over the crack or joint. An application rate of ¼" x ¼" bead of caulk will yield approximately 25 lin. ft. per 10.1oz caulking cartridge. Coverage rate may vary depending on desired thickness and surface to be caulked. Apply when temperatures of the caulk, substrate and ambient air are 40°F and rising.

SPECIFICATIONS:

ASTM D-1227 Type II Class I

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

41 WEB-Caulk (Water-Based Elastomeric Barrier, Low VOC)

CAUTION:

Do not apply to wet surfaces or when rain or freezing temperatures are expected within 24-36 hours. Cold temperatures and high humidity will retard curing. Protect unused product from freezing. Coating must be cured before exposure to water. Store in a heated room between 50°F and 100°F.

Keep container away from heat. Avoid prolonged contact with skin. Wash exposed areas with soap and water. Avoid breathing vapors in confined areas. If product gets into eyes, immediately flush with large amounts of water while holding the eyelids open then seek medical attention. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. Dispose of in an environmentally safe manner. Read Material Safety Data Sheets before using this product.

CARE OF TOOLS:

Tools and caulking gun should be cleaned with soapy warm water immediately after use. Dried caulk will be difficult to remove but can be accomplished by scraping or cleaning with mineral spirits. Take necessary precautions when handling combustible materials.

PACKAGING:

Available in 10.1 oz. caulking cartridges.

VOC:

5gm/L

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>