

45 Sky-Kote

DESCRIPTION:

Karnak 45 Sky-Kote is a 100% acrylic based elastomeric coating. It exhibits exceptional exterior durability, UV stability and superior flexibility in low temperature environments. 45 Sky-Kote dries to a clear, flexible tuff film.

FEATURES, BENEFITS AND ADVANTAGES:

- Easy to apply.
- Quick dry to a water translucent film.
- Will seal scratches and small cracks.
- Hydrophobic water beading film.
- Excellent adhesion.
- Tough, durable film.

USES:

Karnak 45 Sky-Kote is designed for sealing and protecting skylight panels or glass transit windows. 45 Sky-Kote economically provides a quality watertight seal that allows light to pass through.

SURFACE PREPARATION:

All areas to be coated must be clean, dry and free of oil, grease or dirt. Any existing coating must be checked for proper adhesion. Before application, any loosely adhered coating must be removed and surfaces must be properly cleaned and checked for compatibility.

APPLICATION:

Mix lightly prior to application. Apply to surfaces by roof brush, medium nap roller or airless spray equipment.

COVERAGE RATE:

Apply 45 Sky-Kote over the surface at the rate of 1-2 gallons per 100 sq. ft.

PHYSICAL PROPERTIES:

Weight per Gallon:	8.4 lbs.
Solids by Weight:	33%
Color:	Milky White

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

45 Sky-Kote (cont'd)

VOC Content:

Please visit www.karnakcorp.com for latest VOC content as products are updated to comply with the most current VOC regulations

Dry Time:

Less than 24 hours

CAUTION:

Do not apply when rain is imminent. Coating must be dried before exposure to water. Store in a heated room and keep container covered when not in use. Do not thin. Keep out of reach of children. Avoid prolonged contact with skin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

CARE OF TOOLS:

While material is still wet, tools may be cleaned with water. Dry coating can be cleaned with Karna-Klean or similar solvent, taking the necessary precautions when handling flammable materials.

PACKAGING:

Available in 5 gallon pails.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>