

## 535 QS Enviro-Lastic

### BRUSH / ROLLER APPLICATION:

Brush/roller application should be done perpendicular to the base coat for proper protection.

### COVERAGE RATE:

Apply 535 QS Enviro-Lastic at the rate of 1.5 gallons per 100 sq. ft. (24 wet mils) over previously applied coat of 535 QS Enviro-Lastic (if applying two coats of 535 QS Enviro-Lastic allow the first coat to dry 8-24 hours before application of the second coat) or appropriate base coating.

### PHYSICAL PROPERTIES:

Weight Per Gallon: 12 lbs.  
Solids By Weight: 66%  
Solids by Volume: 52%  
Color: White  
Hardness Shore A: 75

### COLOR:

White

### CAUTION:

Do not apply when rain is imminent. Coating must be dried before exposure to water. Store in a heated room and keep container covered when not in use. **Do not thin.** Keep out of reach of children. Avoid prolonged contact with skin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

COLD-PROCESS SYSTEMS AND COATING, EITHER EMULSION OR SOLVENT BASED, SHOULD ONLY BE INSTALLED ON DECKS WITH POSITIVE DRAINAGE.

PER NRCA, (NATIONAL ROOFING CONTRACTORS ASSOCIATION, "THE CRITERIA FOR JUDGING PROPER SLOPE FOR DRAINAGE IS THAT THERE BE NO EVIDENCE OF STANDING WATER ON THE DECK 48 HOURS AFTER IT STOPS RAINING."

### CARE OF TOOLS:

While material is still wet, tools may be cleaned with water. Dry coating can be cleaned with Karna-Klean or xylene or similar solvent, taking the necessary precautions when handling flammable materials.

# KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

## 535 QS Enviro-Lastic

**PACKAGING:**

Available in 5 gallon pails and 55 gallon drums.

**If further information is needed, contact Karnak Technical Services at 1-800-526-4236.**

When installed properly, this product will help reduce energy costs. Actual savings will vary based on geographical location and individual building characteristics. Consult your product manufacturer, roofing contractor, or call 1-888-STAR-YES (1-888-782-7937) for more information.

Please see page 222 for additional mold and safety information.