



# Product Data

## (Asbestos-Free)-Roofing

### #711AF Red "Slaters" Cement

#### DESCRIPTION:

Karnak #711AF Red "Slaters" Cement is a scientifically compounded composition of selected asphalts, pigments, mineral fillers, and refined solvents that are manufactured to a heavy consistency for application by trowel to provide a durable, elastic coating of excellent adhesion and high resistance to water and weathering. This product, when applied, dries to a tough, flexible, waterproof and corrosion proof coating which gives excellent performance over wide ranges of temperature and weather conditions.

#### PHYSICAL PROPERTIES:

1. Consistency: A smooth, heavy trowel consistency which will readily spread on and adhere to vertical and horizontal surfaces without sagging.
2. Character of Dried Film: Uniform, excellent adhesion to masonry, steel, slab insulation and other surfaces.
3. The dried film retains its flexibility and ductility so that the coating will resist extreme variations in temperature and weather.
4. Has excellent resistance to flow at high temperatures when used on a vertical surface.
5. Color: Red

#### USES:

Karnak #711AF Red "Slaters" Cement is a general purpose cement for repairing leaks on slate, shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, down-spouts and cornices. Excellent for sealing cracks in concrete, brick, as a joint filler for pre-cast roof slabs and general purpose use in maintenance of exposed buildings and structures.

#### SPECIFICATIONS:

Federal Specification SS-C-153 Type I (Non-Asbestos)  
ASTM D-4586 Type I (Non-Asbestos)

#### SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil or grease, dust, dirt, loose paint or other foreign matter.

#### APPLICATION:

Spread Karnak #711AF Red "Slaters" Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, spread Karnak #711AF Red "Slaters" Cement over the damaged area, then embed Karnak Cotton, Glass or Poly-Mat Membrane reinforcement and then apply another coat of flashing cement over the entire patch.

(over)

#### KARNAK CORPORATION

330 CENTRAL AVENUE CLARK, NEW JERSEY 07066 732.388.0300 800.526.4236 FAX 732.388.9422 WEB <http://www.karnakcorp.com>

*Other Manufacturing Facilities/Warehouses*

KARNAK SOUTH - FT. LAUDERDALE, FL · KARNAK MIDWEST - CHICAGO, IL · KARNAK NORTHWEST - KENT, WA & PORTLAND, OR

*The above suggested recommendations for use of Karnak products are predicted on tests believed to be reliable. However, since such application and use is beyond our control, we do not guarantee the results to be obtained.*

**CARE OF TOOLS:**

Trowels and other equipment should be thoroughly cleaned with mineral spirits, taking necessary precautions when handling combustible materials.

**CAUTION:**

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

**PACKAGING:**

Available in 5 gallon pails.