

78 Cold Process Cement

DESCRIPTION:

Karnak #78 Cold Process Cement is a multi-purpose fast setting asphalt cement which can be used as a blind nail or lap cement with prepared rolled roofing. Karnak #78 Cold Process Cement can also be used in conjunction with any of Karnak's Cold Process Roofing Systems (i.e.: P-21, P-22) or with other manufacturers' coated fiberglass felts and base sheets.

SURFACE PREPARATION:

All surfaces to be coated should be dry and free of all dust, dirt or other loose debris.

APPLICATION:

Under normal conditions, Karnak #78 Cold Process Cement should be applied by brush at the rate of 2 to 3 gallons per 100 sq. ft. On large roof areas Karnak #78 Cold Process cement can be brushed, squeegeed or sprayed using airless sprayequipment. Application should be made at the rate of 1 to 2 gallons per 100 sq. ft.

SPECIFICATIONS:

ASTM D-3019 Type III

ASTM D-4479 Type I

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

CARE OF TOOLS: Tools should be thoroughly cleaned with mineral spirits or Karna-Klean, taking necessary precautions when handling combustible materials.

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



FM1015