

89 Sta-Tack Primer

DESCRIPTION:

Karnak #89 Sta-Tack Primer is a waterbased polymer modified primer for self-adhering membranes. Karnak #89 Sta-Tack Primer penetrates pores and dries fast to provide a tacky surface.

FEATURES, BENEFITS AND ADVANTAGES:

1. Easy to apply.
2. Quick drying.
3. Promotes adhesion.
4. Use as is, needs no intermixing.
5. VOC compliant.

USES:

Karnak #89 Sta-Tack Primer is designed for use as a primer prior to the installation of self-adhering membranes. This thin solution readily penetrates pores and dries fast to provide a tacky, firm substrate for adhesion of the membranes.

Karnak #89 Sta-Tack Primer is suitable for use over asphalt, wood, plywood, gypsum board and concrete surfaces.

SURFACE PREPARATION:

All surfaces to be primed must be dry and free from dust, dirt, oil, grease and any other foreign matter.

APPLICATION:

Easily applied by brush, roller or hand sprayer at the rate of 0.20 (1/5th) gallon per 100 sq.ft. (500 sq.ft. per gallon).

COVERAGE RATE:

Apply at the rate of 0.20 gallon per 100 sq.ft.

PHYSICAL PROPERTIES:

Weight per Gallon:	8.61 lbs.
Solids by Weight:	37%
Color:	Blue
Dry Time:	33 minutes @ 77°F and 50% RH
Cure Time:	2 hours @ 77°F and 50% RH
Service Temp:	-40°F and 160°F
Coverage:	0.20 gal. per 100sq.ft.
Application Temperatures:	40°F and rising.
VOC's:	Please visit www.karnakcorp.com for latest VOC content as products are updated to comply with the most current VOC regulations

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
 732-388-0300 • 800-526-4236 • FAX: 732-388-9422
 WEB: <http://www.karnakcorp.com>

89 Sta-Tack Primer

CAUTION:

Do not apply when rain is imminent. **Protect from freezing.** Primer must be dried before exposure to water. Store between 50°F and 100°F. Keep container covered when not in use. **Do not thin.** Keep out of reach of children. Do not take internally. Harmful if swallowed. Avoid contact with eyes and skin. Dispose of in an environmentally safe manner. Cover air intake during application and while drying.

CARE OF TOOLS:

Uncured materials may be cleaned with water. Cured material may be cleaned with Karna-Klean, mineral spirits or similar solvent.

PACKAGING:

Available in 1 gallon and 5 gallon pails.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>